

## Dell EqualLogic PS 6000 and PS 4000 Attributes Compared

	PS6000E	PS6500E	PS6000X	PS6000XV	PS6000S	PS4000E	PS4000X	PS4000XV
<b>Array Capacity</b>	2, 4, 8 or 16TB	24 TB or 48 TB	6.4, 7.2 or 9.6 TB	4.8 or 7.2	400GB or 800GB	2, 4, 8 or 16 TB	6.4, 7.2, 9.6, TB	4.8 or 7.2TB
<b>Disk Drives</b>	8 or 16-7,200RPM Sata Drives	48--7,200 RPM Sata Drive	16--10,000 RPM SAS Drives	16--15,000 RPM Sas Drives	16 Solid State Disk (SSD) Drives	8 or 16-7,200 RPM Sata Drives	16-10,000 RPM SAS Drives	16-15,000 RPM SAS Drives
<b>Drive Capacities</b>	250 GB, 500 GB or 1TB	500GB or 1TB	400, 450 or 600GB	300 or 450GB	50GB	250 GB, 500GB or 1 TB	400 GB, 450 GB or 1 TB	300 GB or 450 GB
<b>Full Hardware Redundancy</b>	Yes	Yes				Yes	Yes	
<b>Network connectivity</b>	4 Ethernet/iSCSI Ports Per Controller					2 Ethernet/iSCSI ports per Controller for I/O; 1 Ethernet port of management		
<b>Chassis</b>	3U	4U	3U	3U	3U	3U	3U	3U
<b>Memory</b>	2 GB or 4 GB	4 GB	4 GB	4 GB	4 GB	2 GB or 4 GB	4 GB	4 GB
<b>Maximum # of Arrays Per PS Series Group</b>	12 PS arrays, including up to 2 PS4000 Arrays					2 PS4000 Arrays		
<b>Enterprise Data Services</b>	Yes, all inclusive with no seperate licenses on all PS Series arrays							

